

Please contact Invacare EU Export Customer Services on :-
Tel : +33 247 626980 ; Email : serviceclient_export@invacare.com
 Or visit our website : www.invacare.eu.com



Küschall K-Series



Active, lightweight aluminum wheelchair, rigid frame, folding and angle-adjustable backrest



Description:

- Aluminum frame with hydroformed tubes
- Customization kit with premium decals
- Backrest adjustable in angle and folding on the seat with locking as standard
- Max user weight: 130 kg
- Complete weight: from 7.8 kg.
- Transport weight: from 5.1 kg.
- Warranty: 2 years excluding wearing parts

Discover our new tool to help calculate overall dimensions and find the visual configurator to make your configuration!

ALL FRAME COLORS &
DECALS/STYLINGS FOR FREE UNTIL
END OF JUNE!

Date :

Purchase Order :

Customer Code :

Distributor Stamp:

We reserve the right to deliver a + or - tolerance of +/- 10 mm on all measurements We reserve the right to make technical changes without notice


☐ Please make your selection with a cross in the box

◆ Standard feature


○ Free of charge option

CODE		DESCRIPTION	NC : Non Compatible NC : 9999 = not compatible with the reference 9999	Euros	
DKA0067	☐	küschall® K-Series®		2 927,96	
SPECIAL CONSTRUCTION					
DKA0000	☐	Myküschall special construction		On Request	
PACKS POSITIONNEMENT ET PRÉVENTION D'ESCARRES					
DKA0220	☐	Matrx MX2 & Libra positioning and pressure ulcer prevention pack including: - Matrx MX2 (size of your choice DKA2300 to DKA2315) - Matrx Libra cushion (DKA2720) - Bodypoint® Evoflex® 2-point hip belt (size of your choice DKA7810 to DKA7830)	NC: Seat width 360 mm possible only with depth 400/425 mm, 1310, 1315, 1350, 1355, 1410, 1420	1222,23	Save 15% by selecting this PACK, i.e. €277,53
DKA0230	☐	Matrx Elite E2 & Libra positioning and pressure ulcer prevention pack including: - Matrx Elite E2 / Elite Deep E2 backrest (size of your choice DKA2320 to DKA2350) - Matrx Libra cushion (DKA2720) - Bodypoint® Evoflex® 2-point hip belt (size of your choice DKA7810 to DKA7830)	NC: Seat width 360 mm possible only with depth 400/425 mm, 1310, 1315, 1410, 1420	910,24	Save 10% by selecting this PACK, i.e. €106,70
SEATING CHOICE					
FRAME					
DKA1040	☐	Frame Angle 75° To The Ground Aluminium	NC : 1475, 1490, 1495, 7240	◆	 Châssis 90° : 1070
DKA1050	☐	Frame Angle 75° To The Ground Aluminium - Tapered Front Frame	NC : 1475, 1490, 1495, 1740, 1745, 1750, 3230, 7240	○	
DKA1060	☐	Frame Angle 75° To The Ground Aluminium +50Mm	NC : 1410, 1420, 1435, 1740, 1745, 1750, 1755, 1760	145,97	
DKA1070	☐	Frame Angle 90° To The Ground Aluminium	NC : 1475, 1490, 1495, 7240	217,06	
DKA1080	☐	Frame Angle 90° To The Ground Aluminium - Tapered Front Frame	NC : 1475, 1490, 1495, 1740, 1745, 1750, 3230, 5300, 5350, 5400, 5450, 5500, 7240	217,06	
DKA1090	☐	Frame Angle 90° To The Ground Aluminium +50 Mm	NC : 1410, 1420, 1435, 1740, 1745, 1750, 1755, 1760	217,06	


SUSPENSION				
DKA1200	☐	40 - 65 kg	NC : 1310, 1350, 1355, 1410, 1520, 1815, 1820, 1825, 1830, 1835, 6030, 6040, 6420, 6430, 6950	336,49
DKA1210	☐	65 - 85 kg	NC : 1310, 1350, 1355, 1410, 1520, 1815, 1820, 1825, 1830, 1835, 6030, 6040, 6420, 6430, 6950	336,49
DKA1220	☐	85 - 100 kg	NC : 1310, 1350, 1355, 1410, 1520, 1815, 1820, 1825, 1830, 1835, 6030, 6040, 6420, 6430, 6950	336,49
SEAT WIDTH (SW)				
DKA1310	☐	320 mm	NC : 2000, 2050, 2300 to 2357, 2610, 2630, 2710, 2720, 2740, 2742, 2744, 2746, 2748, 3405, 3420	○
DKA1315	☐	340 mm	NC : 2300 to 2357, 2710, 2720, 2740, 2742, 2744, 2746, 2748, 3405, 3420	○
DKA1320	☐	360 mm	NC : 2364, 2366, 2368, 2372, 2710, 2742, 2744, 2746, 2748	○
DKA1325	☐	380 mm	NC : 2366, 2368, 2370, 2372	○
DKA1330	☐	400 mm	NC : 2360, 2366, 2368, 2370, 2372	○
DKA1335	☐	420 mm	NC : 2360, 2362, 2368, 2370, 2372	○
DKA1340	☐	440 mm	NC : 2210, 2360, 2362, 2364, 2370, 2372, 2630, 2740, 2742	○
DKA1345	☐	460 mm	NC : 2210, 2360, 2362, 2364, 2372, 2630, 2740, 2742, 2744	○
DKA1350	☐	480 mm	NC : 2210, 2300, 2305, 2310, 2315, 2345, 2360, 2362, 2364, 2366, 2630, 2740, 2742, 2744, 3230	○
DKA1355	☐	500 mm	NC : 2210, 2300, 2305, 2310, 2315, 2345, 2360, 2362, 2364, 2366, 2368, 2630, 2740, 2742, 2744, 2746, 3210, 3230	○
SEAT DEPTH (SD)				
DKA1410	☐	350 mm	NC : 1500, 1510, 2630, 2710, 2720, 2740 to 2746, 2748, 2860, 7810, 7820, 7830	○
DKA1420	☐	375 mm	NC : 2710, 2720, 2742, 2744, 2746, 2748, 7810, 7820, 7830	○
DKA1435	☐	400 mm		○
DKA1450	☐	425 mm	NC : 2740, 2746	○
DKA1465	☐	450 mm	NC : 2630, 2740, 2742	○
DKA1475	☐	475 mm	NC : 2630, 2740, 2742, 2744, 2748	○
DKA1490	☐	500 mm	NC : 2630, 2710, 2740, 2742, 2744, 2746, 2748	○
DKA1495	☐	525 mm	NC : 2610, 2630, 2710, 2740, 2742, 2744, 2746, 2748	○
SEAT POSITION (SP)				
DKA1500	☐	Position 1 = 140 mm (MOST active)		○
DKA1510	☐	Position 2 = 125 mm		○
DKA1520	☐	Position 3 = 110 mm		◆
DKA1530	☐	Position 4 = 95 mm		○
DKA1540	☐	Position 5 = 80 mm (Least stable)		○



BACK HEIGHT (BH)						
DKA1600	☐	Backrest height according to chosen Matrix backrest		NC : 2100, 2210, 2220, 2230	○	
DKA1605	☐	270 mm		NC : 2150, 2240, 2430, 0703, 7600	○	
DKA1610	☐	285 mm		NC : 2150, 2240, 7600	○	
DKA1615	☐	300 mm	DKA1620 ☐	315 mm	NC : 2150, 2240, 7600	○
DKA1625	☐	330 mm	DKA1630 ☐	345 mm	NC : 2150, 2240, 7600	○
DKA1635	☐	360 mm		NC : 2150, 2210, 2240, 7600	○	
DKA1640	☐	375 mm		NC : 2150, 2210, 2240, 7600	◆	
DKA1645	☐	390 mm		NC : 2150, 2210, 2240, 7600	○	
DKA1650	☐	405 mm	DKA1655 ☐	420 mm	NC : 2150, 2210, 2240	○
DKA1660	☐	435 mm	DKA1665 ☐	450 mm	NC : 2150, 2210, 2240	○
DKA1670	☐	465 mm	DKA1675 ☐	480 mm	NC : 2150, 2210, 2240	○
Front seat height (FSTF) - see table 1 of front wheel compatibility and front seat height						
DKA1740	☐	450 mm		NC : 5300, 5350, 5400, 5450, 5500	○	
DKA1745	☐	460 mm		NC : 5300, 5350, 5400, 5450, 5500	○	
DKA1750	☐	470 mm			○	
DKA1755	☐	480 mm			○	
DKA1760	☐	490 mm			○	
DKA1765	☐	500 mm			◆	
DKA1770	☐	510 mm			○	
DKA1775	☐	520 mm			○	
REAR SEAT-TO-FLOOR (RSTF)						
DKA1815	☐	390 mm		NC : 3490, 3495, 6030, 6040, 6420, 6430	○	
DKA1820	☐	400 mm		NC : 3490, 3495, 6030, 6040, 6430	○	
DKA1825	☐	410 mm		NC : 3490, 3495	○	
DKA1830	☐	420 mm			○	
DKA1835	☐	430 mm			◆	
DKA1840	☐	440 mm	DKA1845 ☐	450 mm	○	
DKA1850	☐	460 mm	DKA1855 ☐	470 mm	○	
DKA1860	☐	480 mm			○	
DKA1865	☐	490 mm		NC : 6410	○	
LOWER LEG LENGTH (LLL) - FOR LLL < 390MM AND DEPENDING ON CONFIGURATION, FOOTPLATE MAY BE UP MOUNTED, SEE TABLE 2						
DKA1918	☐	290 mm			○	
DKA1920	☐	300 mm	DKA1922 ☐	310 mm	○	
DKA1924	☐	320 mm	DKA1926 ☐	330 mm	○	
DKA1928	☐	340 mm	DKA1930 ☐	350 mm	○	
DKA1932	☐	360 mm	DKA1934 ☐	370 mm	○	
DKA1936	☐	380 mm	DKA1938 ☐	390 mm	○	
DKA1940	☐	400 mm	DKA1942 ☐	410 mm	○	
DKA1944	☐	420 mm			○	
DKA1946	☐	430 mm			◆	
DKA1948	☐	440 mm	DKA1950 ☐	450 mm	○	
DKA1952	☐	460 mm	DKA1954 ☐	470 mm	○	
DKA1956	☐	480 mm			○	
BACKREST						
BACKREST MATERIAL						
DKA2000	☐	Aluminium		NC : SW 320 mm	◆	
DKA2050	☐	Titanium = - 80 g (with aluminum push handles)		NC : SW 320 mm, 2150, 2430, 7600	345,02	
BACKREST TYPE						
DKA2100	☐	Standard		NC : 2240, 2300 to 2357, 2440	◆	
DKA2150	☐	BACKREST WITH LOWER BACKBRACE, BACKREST TUBES HEIGHT IS 285 MM		NC : 2210, 2220, 2230, 2430	○	





LLL = LLL patient - Seat cushion



BACK UPHOLSTERY					 2230
DKA2210	☐	LIGHT BACK UPHOLSTERY	NC : 2300 to 2357, 2430, 2440 and SW > 420 mm / BH > 345 mm	178,20	
DKA2220	☐	TENSION ADJUSTABLE PREMIUM BLACK BACK UPHOLSTERY WITH LOOP BANDS	NC : 2300 to 2357, 2440	◆	
DKA2230	☐	AERO BACK, TENSION ADJUSTABLE	NC : 2300 to 2357, 2440	258,77	
DKA2240	☐	WITHOUT BACKREST UPHOLSTERY, SELECT IF YOU WANT TO MOUNT POSITIONNING BACKRESTS SUCH AS MATRX		○	
MATRX BACKRESTS - HEIGHT REFERS TO ACTUAL HEIGHT OF THE MATRX BACKREST, NOT POSSIBLE WITH SW ≤ 340 MM					 2300, 2305, 2310, 2315
DKA2300	☐	Matrx MX2, Height 150 Mm With Quick Release Hardware	NC : 2370, 2372	927,01	
DKA2305	☐	Matrx MX2, Height 230 Mm With Quick Release Hardware	NC : 2370, 2372	927,01	
DKA2310	☐	Matrx MX2, Height 305 Mm With Quick Release Hardware	NC : 2370, 2372	927,01	
DKA2315	☐	Matrx MX2, Height 405 Mm With Quick Release Hardware	NC : 2370, 2372	927,01	
DKA2316	☐	Elite Deep E2 , Height 160 Mm With Mini-Set Mounting Hardware		500,47	 2316 to 2331
DKA2317	☐	Elite Deep E2 , Height 210 Mm With Mini-Set Mounting Hardware		500,47	
DKA2318	☐	Elite Deep E2 , Height 260 Mm With Mini-Set Mounting Hardware		500,47	
DKA2320	☐	Elite Deep E2 , Height 310 Mm With Mini-Set Mounting Hardware		500,47	
DKA2322	☐	Elite Deep E2, Height 360 Mm With Mini-Set Mounting Hardware		500,47	
DKA2325	☐	Elite Deep E2, Height 410 Mm With Mini-Set Mounting Hardware		500,47	 2332 to 2357
DKA2330	☐	Elite Deep E2, Height 460 Mm With Easy-Set Mounting Hardware		500,47	
DKA2331	☐	Elite Deep E2, Height 510 Mm With Easy-Set Mounting Hardware		500,47	
DKA2332	☐	Elite E2, Height 160 Mm With Mini-Set Mounting Hardware		500,47	
DKA2334	☐	Elite E2, Height 210 Mm With Mini-Set Mounting Hardware		500,47	
DKA2335	☐	Elite E2, Height 260 Mm With Mini-Set Mounting Hardware		500,47	
DKA2340	☐	Elite E2, Height 310 Mm With Mini-Set Mounting Hardware		500,47	
DKA2345	☐	Elite E2, Height 360 Mm With Mini-Set Mounting Hardware		500,47	
DKA2350	☐	Elite E2, Height 410 Mm With Mini-Set Mounting Hardware		500,47	
DKA2355	☐	Elite E2, Height 460 Mm With Easy-Set Mounting Hardware		500,47	
DKA2357	☐	Elite E2, Height 510 Mm With Easy-Set Mounting Hardware		500,47	
MATRX BACKRESTS WIDTH CHOICE - See Table 3					
DKA2360	☐	360 mm - indicative bust 265 mm		○	
DKA2362	☐	380 mm - indicative bust 290 mm		○	
DKA2364	☐	410 mm - indicative bust 315 mm		○	
DKA2366	☐	430 mm - indicative bust 340 mm		○	
DKA2368	☐	460 mm - indicative bust 370 mm		○	
DKA2370	☐	480 mm - indicative bust 390 mm		○	
DKA2372	☐	510 mm - indicative bust 420 mm		○	

MX2: only 140g more than a tension-adjustable backrest!

PUSH HANDLES						
DKA2400	☐	WITHOUT PUSH HANDLES		◆		
DKA2410	☐	PUSH HANDLES FIXED, SHORT		○		
DKA2420	☐	PUSH HANDLES FIXED, LONG		○		
DKA2430	☐	HEIGHT ADJUSTABLE, REAR SET	NC : BH 285 mm to 330 mm + 3480, 3480	212,32		
DKA2440	☐	HEIGHT ADJUSTABLE, INTEGRATED		254,03		
DKA2450	☐	FOLDABLE PUSH HANDLES	NC : BH 315 mm to 330 mm + 3480	213,27		
BACKREST ANGLE (BA)						
DKA2520	☐	78°		○		
DKA2540	☐	82°		◆		
DKA2560	☐	86°		○		
DKA2580	☐	90°	DKA2590 ☐ 94°	○		
SEAT UPHOLSTERY						
DKA2600	☐	STANDARD SEAT UPHOLSTERY - CENTRAL LOOP BAND		◆		
DKA2610	☐	TENSION ADJUSTABLE WITH ONE CENTRAL LOOP BAND		92,89		
DKA2630	☐	LIGHT SEAT UPHOLSTERY		66,35		
SEATING						
SEAT CUSHION						
DKA2700	☐	STANDARD SEAT CUSHION,60 MM, DOUBLE FOAM WITH VISCO TOP		NC : 2810, 2820, 2830, 2840, 2850		101,42
DKA2710	☐	FLO-TECH LITE		NC : 2810, 2820, 2830, 2840, 2850		118,48
DKA2720	☐	MATRIX LIBRA CUSHION, BLACK SMOOTH COVER		NC : largeur 360 mm possible uniquement avec profondeur 400 and 425 mm		293,84
DKA2740	☐	CLASSIC VISCO CUSHION 375 X 400 MM		NC : 2810, 2820, 2830, 2840, 2850		76,78
DKA2742	☐	CLASSIC VISCO CUSHION 405 X 400 MM		NC : 2810, 2820, 2830, 2840, 2850		65,40
DKA2744	☐	CLASSIC VISCO CUSHION 405 X 400 MM		NC : 2810, 2820, 2830, 2840, 2850		65,40
DKA2746	☐	CLASSIC VISCO CUSHION 455 X 400 MM		NC : 2810, 2820, 2830, 2840, 2850		76,78
DKA2748	☐	CONTOUR VISCO NG CUSHION		NC : 2810, 2820, 2830, 2840, 2850		76,78
SEAT BAG						
DKA2800	☐	SEAT BAG, CLICK-IN AND REMOVABLE			81,52	
MATRIX LIBRA CUSHION ACCESSORIES						
DKA2810	☐	FLUID SUPPLEMENT SAC (PAIR)			91,00	
DKA2820	☐	TAPERED WEDGE PAIR			41,71	
DKA2830	☐	ABDUCTOR			47,39	
DKA2840	☐	LATERAL SIDE WEDGE			41,71	
DKA2850	☐	ANTERIOR FRONT WEDGE			54,98	
Base rigide						
DKA2860	☐	SEAT RIGIDIZER			56,87	
SEAT UPHOLSTERY BAGS						
DKA2910	☐	BIG BAG - TO FIX UNDER THE SEAT			61,61	

FOOTREST					 3200
FOOTREST TYPE (TUBE / PLATE)					
DKA3200	☐	FOOTREST TUBE, RIGID - ALUMINIUM NEW PROFILE		◆	
DKA3210	☐	FOOTREST TUBE, RIGID - TITANIUM		246,45	
DKA3220	☐	CARBON FOOTPLATE, ANGLE ADJUSTABLE	NC : 3290	264,45	
DKA3230	☐	FOOTPLATE FLIP-UP TO SIDE, ANGLE ADJUSTABLE NOT POSSIBLE WITH TAPERED FRAME	NC : 3290	458,77	
FOOTREST COVER					 3305
DKA3290	☐	FOOTREST COVER		113,74	
CALF STRAP MOUNTED ON THE FRAME					
DKA3300	☐	CALF STRAP MOUNTED ON THE FRAME		◆	
DKA3305	☐	CALF STRAP WITH BRACKET SUPPORT		76,78	
CLOTHES GUARDS / MUDGUARDS					
CLOTHES GUARDS					 3440
DKA3405	☐	ECONOMY CLOTHES GUARDS, FLIP-BACK - NEW PART		◆	
DKA3420	☐	CARBON CLOTHES GUARDS, FLIP BACK - NEW DESIGN		167,77	
MUDGUARDS					 3480 3490
DKA3440	☐	CARBON MUDGUARDS, REMOVABLE- NEW DESIGN	NC : 3490, 3495	336,49	
DKA3450	☐	ECONOMY MUDGUARDS, REMOVABLE - NEW DESIGN	NC : 3490, 3495	○	
ARMREST / SIDEREST					
DKA3480	☐	TUBULAR ARMREST, NON-LOCKING, HEIGHT ADJUSTABLE, REMOVABLE, SWING-AWAY, COMFORT PADDED	NC : BH < 315 mm + 2450, BH <315 + 2430, 6950	264,45	
DKA3490	☐	SIDEREST, HEIGHT ADJUSTABLE, SHORT, NON-LOCKING	NOT POSSIBLE WITH RSTF < 420 MM	253,08	
DKA3495	☐	SIDEREST, HEIGHT ADJUSTABLE, LONG, NON-LOCKING	NOT POSSIBLE WITH RSTF < 420 MM	277,73	
FRAME					FOR FREE! EXTRA LEAD TIME +10 DAYS
FRAME COLOR					
DKA4000	☐	SPACE BLACK (RAL 9005)		○	
DKA4010	☐	ANTHRACITE GREY (RAL 7016)		○	
DKA4020	☐	PURE WHITE (RAL 9016)	NC : 4220	○	
DKA4030	☐	CARMINE RED (RAL 3002)		○	
DKA4040	☐	AZURE BLUE (RAL 5017)		○	
DKA4060	☐	FLASHY YELLOW (RAL 1016)			
DKA4070	☐	ATOMIC VIOLET - specific color mix, no RAL definition			
DKA4100	☐	BLACK GLOSSY (RAL 9005)			
DKA4130	☐	SILVER GREY (RAL 9006)			
DKA4140	☐	ROYAL BLUE - specific color mix, no RAL definition			
DKA4150	☐	RUBY RED (RAL 3003)			
DKA4170	☐	DYNAMITE ORANGE - specific color mix, no RAL definition			
DKA4180	☐	FOREST GREEN (RAL 6029)			
DKA4050	☐	Special colors on demand only : - Manufacturing time + 10 days: for a color already offered on the other ranges of Invacare manual wheelchairs. WHERE - Manufacturing time + 15 days: for any other request (subject to feasibility) - specify RAL number		473,93	 BOLD  TAG
STYLING					
DKA4190	☐	BOLD	NC : 4300, 4310	FOR FREE!	
DKA4195	☐	TAG	NC : 4200 to 4250	◆	
BOLD COLOR					
DKA4200	☐	BLACK		○	
DKA4210	☐	DARK GREY		○	
DKA4220	☐	LIGHT GREY		○	
DKA4230	☐	RED		○	
DKA4240	☐	BLUE		○	
DKA4250	☐	GOLD		○	

TAG COLOR			
DKA4300	☐	BLACK	○
DKA4310	☐	RED	○
FRONT WHEELS			
DKA5000	☐	3" SUPERSPORT	○
DKA5050	☐	4" EVERYDAY WHEEL WITH BLACK TYRE	◆
DKA5100	☐	4" COMFORT WHEEL WITH BLACK TYRE	○
DKA5150	☐	4" STAREC BLACK HUB, BLACK TYRE	75,83
DKA5200	☐	4" FROGLEGS FRONT WHEEL WITH BLACK HUB, BLACK TYRE	121,33
DKA5250	☐	4" FROGLEGS FRONT WHEEL WITH SILVER HUB, BLACK TYRE	121,33
DKA5300	☐	5" EVERYDAY WITH BLACK RUBBER HUB, BLACK TYRE	○
DKA5350	☐	5" COMFORT WHEEL BLACK RUBBER HUB, BLACK TYRE	○
DKA5400	☐	5" STAREC BLACK HUB, BLACK TYRE	103,32
DKA5450	☐	5" FROGLEGS FRONT WHEEL WITH BLACK HUB, BLACK TYRE	147,87
DKA5500	☐	5" FROGLEGS FRONT WHEEL WITH SILVER HUB, BLACK TYRE	147,87
REAR WHEEL FIXATION			
DKA6020	☐	STANDARD REAR WHEEL POSITION	NC : 6100 to 6140, 6230, 6240
DKA6030	☐	LIGHT REAR WHEEL EXTENSION (POSITION 1 TO 3)	NC : 6070, 6130, 6140, 6230, 6240
DKA6040	☐	REAR WHEEL EXTENSION (5 POSITIONS)	NC : 6070
CAMBER AXLE TYPE - 1st AXLE			
DKA6050	☐	VARIO-AX, ADJUSTABLE CAMBER 1 / 3 / 7 / 10°	NC : 6200, 6210, 6220, 6270, 6950, 7230
DKA6060	☐	STANDARD AXLE	◆
DKA6070	☐	CARBON AXLE	NC : 6950
POSITION OF 1st AXLE			
DKA6100	☐	1 (compulsory for the use of a 2nd axle)	○
DKA6110	☐	2	NC : 6230, 6240
DKA6120	☐	3	NC : 6230, 6240
DKA6130	☐	4	NC : 6230, 6240
DKA6140	☐	5	NC : 6230, 6240
CAMBER ANGLE 1st AXLE			
DKA6200	☐	0°	NC : 6270
DKA6210	☐	3°	◆
DKA6220	☐	6°	NC : 6240, 6250, 6950
SECOND CAMBER AXLE TYPE - SECOND AXLE ONLY IN THE 5TH POSITION FROM THE FRONT			
DKA6230	☐	STANDARD	NC : 6950
DKA6240	☐	VARIO-AX, ADJUSTABLE CAMBER 1 / 3 / 7 / 10°	NC : 6250, 6260, 6270, 6950, 7230
CAMBER ANGLE 2nd AXLE - MAX. 3° CAMBER DIFFERENCE WITH 1ST AXLE ; IF ONLY ONE OF THE AXLES IS A VARIO-AX, 2ND AXLE ONLY IN 0 OR 3°			
DKA6250	☐	0°	○
DKA6260	☐	3°	○
DKA6270	☐	6°	○
QUAD RELEASE AXLE			
DKA6300	☐	TETRA-CLIP	NC : 6550, 6950
			143,13
REAR WHEELS SIZE (see the possible diameters per wheel in Type of rear wheels)			
DKA6410	☐	24"	◆
DKA6420	☐	25"	NC : 6500, 6510, 6600, 6610, 6630, 6660, 6680, 6700, 6710, 6720, 6760, 6770, 6900, 6910, 6950
DKA6430	☐	26"	NC : 6500, 6520, 6550, 6600, 6610, 6630, 6660, 6720, 6740, 6750, 6760, 6770, 6950, 7240



5000




5200 / 5250 / 5450 / 5500



5350

5050 / 5300



Pos.1-3

Pos.1-5



6300

REAR WHEELS TYPE					
DKA6500	☐	24" ACTIVE WHEELS (BLACK RIM, HUB AND RADIAL SPOKING INCL. ALU HANDRIMS & LIGTH TYRE GREY)	24"	NC : All handrims, 6680, 6900, 6910	◆
DKA6510	☐	KUSCHALL STAREC HUB (BLACK RIM AND HUB, BLACK CROSS SPOKING INCL. ALU HANDRIMS & LIGTH TYRE GREY)	24", 26"		○
DKA6520	☐	HIGH PERFORMANCE (BLACK RIM, BLACK STAREC HUB, BLACK CROSS SPOKING INCL. ALU HANDRIMS & LIGTH TYRE GREY)	24", 25"	NC : 6660	533,65
DKA6550	☐	SPINERGY LXX (BLACK RIM, HUB AND RADIAL SPOKING INCL. ALU HANDRIMS & LIGTH TYRE GREY)	24", 25"	NC : 6660, 6910	771,56
REAR WHEEL TYRE					
DKA6600	☐	MAXXIS LITE GUARD BLACK TYRE (puncture protection)	24"		◆
DKA6625	☐	MAXXIS ALPHA PROTECT BLACK TYRE (puncture protection)	24"		72,04
DKA6630	☐	MBL SPEEDLITE (puncture protection)	24"		72,04
DKA6660	☐	SOLID TYRE, BLACK	24"	NC : 6680, 7230	72,04
HANDRIMS					
DKA6700	☐	ANTI-SLIP DIST. 3 CM ADJUSTABLE 4CM	24", 26"		142,18
DKA6710	☐	STEEL, DIST. 3 CM ADJUSTABLE 4CM	24", 26"		113,74
DKA6720	☐	TITANIUM, DIST. 3 CM ADJUSTABLE 4CM	24"		277,73
DKA6740	☐	CARBOLIFE GEKKO , WITH ANTI-SLIP DIST. 3 CM ADJUSTABLE 4CM	24", 25"		373,46
DKA6750	☐	CARBOLIFE GEKKO S , WITH ANTI-SLIP DIST. 3 CM ADJUSTABLE 4CM	24", 25"		373,46
DKA6760	☐	CARBOLIFE CURVE L WITH ERGONOMIC PROFILE DIST. 3 CM ADJUSTABLE 4CM	24"		282,46
DKA6770	☐	CARBOLIFE QUADRO , WITH ERGONOMIC PROFILE DIST. 3 CM ADJUSTABLE 4CM	24"		373,46
DKA6780	☐	LIGHT ALU, GREY, DIST. 3 CM ADJUSTABLE 4CM	24", 25", 26"		◆
DKA6790	☐	LIGHT ALU, BLACK, DIST. 3 CM ADJUSTABLE 4CM	24", 25", 26"		○



6790 6760



6700 6710



6720



6740

SPOKE GUARDS				
DKA6900	☐	Transparent	24", 26"	200,95
DKA6910	☐	Black	24", 26"	200,95
ALBER ADD-ON KIT - 2 ALBER ANTI-TIPPERS INCLUDED / ONLY FOR 24" REAR WHEELS ALBER ADDS ON KIT + 3° CAMBER AXLE : MAX USER WEIGHT 100 Kg				
DKA6950	☐	E-MOTION & TWION M25 ADAPTER PLATE	NC : 7500, 7510, 7520, 8200, 8210, 8300	579,15
Tip : for perfect compatibility of the brakes with the manual wheels, we advise you to equip them with the same coating as the motorized wheels.				
BRAKES				
DKA7210	☐	PUSH BRAKE, LEVER BENT		◆
DKA7230	☐	PERFORMANCE BRAKE	NC : 7300	76,78
DKA7240	☐	ACTIVE BRAKE	NC : 7300	76,78
DKA7250	☐	LIGHT ACTIVE BRAKE	NC : 7300	145,02
BRAKE EXTENSION LEVER				
DKA7300	☐	EXTENSION LEVER FOR STANDARD BRAKE		76,78
SAFETY OPTIONS				
MAX. 2 ADAPTATIONS PER SIDE (ADAPTATIONS=ANTITIPPER, TIPPER AID, CANE HOLDER, TRANSIT WHEELS)				
ANTI TIPPER				
DKA7500	☐	ANTITIPPER TUBE, RIGHT		130,81
DKA7510	☐	ANTITIPPER TUBE, LEFT		130,81
DKA7520	☐	ANTITIPPER TUBE, BOTH SIDES	NC : 8300	261,61
TRANSPORTATION KIT				
DKA7600	☐	TRANSPORTATION KIT INCL. POSTURE BELT AND LABELS	NC : BH ≤ 400 mm, 7800	57,82
BELT				
DKA7800	☐	STANDARD BELT - PLASTIC BUCKLE		42,65
DKA7810	☐	BODYPOINT POSTURE BELT EVOFLEX, 2 POINTS, SMALL, FLAT-MOUNT WITH PUSH BUTTON		217,06
DKA7820	☐	BODYPOINT POSTURE BELT EVOFLEX, 2 POINTS, MEDIUM, FLAT-MOUNT WITH REHAB LATCH		217,06
DKA7830	☐	BODYPOINT POSTURE BELT EVOFLEX, 2 POINTS, LARGE, FLAT-MOUNT WITH REHAB LATCH		217,06
PASSIVE LIGHTS				
DKA7900	☐	PASSIVE LIGHTS, ASSEMBLED		22,75
ATTENDANT OPTIONS				
FRAME PROTECTION				
DKA8010	☐	FRONT FRAME PROTECTION		44,55
CANE HOLDER				
DKA8200	☐	CANE HOLDER, RIGHT		66,35
DKA8210	☐	CANE HOLDER, LEFT		66,35
TRANSIT WHEELS				
DKA8300	☐	TRANSIT WHEELS		301,42
OTHERS OPTIONS				
DKA8500	☐	AIR PUMP - NEW	NOT POSSIBLE WITH SW 340 MM	33,18
DKA8550	☐	TOOL KIT		22,75
DKA8650	☐	WHEELS BAG		65,40
DKA8680	☐	24" MOUNTAIN BIKE WHEELS WITH BAG -MOUNTAIN BIKE WHEELS AND TIRES WITH ALU GREY HANDRIMS ; QUICK RELEASE AXLES INCLUDED		646,45
DKA8800	☐	BODYPOINT CALF STRAP		104,27
DKA8850	☐	BODYPOINT MOBILITY BAG		104,27



7210 7230 7240



7250



7500 / 7520



Evoflex belt adjustable from 35 mm to 125 mm rearward from the front of the seat sling. 6 positions in 15 mm increments



7810 / 7820 / 7830



8300



8550



8680

RAMPS


1440530	☐	Fiberglass Folding Mono Ramp Folded dimensions: 2000 x 230 mm 16.3 kg - maximum capacity: 300 kg		1 787,68
1654128	☐	Basic ramp 2 telescopic parts in aluminum and non-slip coating Folded dimensions: 1210 x 194 mm 8.8 kg per pair - maximum capacity: 270 kg		402,84
1654129	☐	Quick2go Compact 3-part aluminum telescopic ramp with non-slip coating Folded dimensions: 870 x 237 mm 13.6 kg per pair - max. : 260 kg		805,69
1654130	☐	Aluminum Folding Mono Ramp Folded dimensions: 1824 x 714 mm 13.9 kg - maximum capacity: 300 kg		426,54



1440530



1654128



1654129



1654130

Table 1
Frame type/angle/length, rear wheel size, front wheel size

Frame	24" rear wheel			25" rear wheel			26" rear wheel		
	front wheel			front wheel			front wheel		
	3"	4"	5"	3"	4"	5"	3"	4"	5"
75° Short									
75° Standard									
75° +50mm									
90° Short									
90° Standard									
90° +50mm									
75° tapered									
90° tapered									

Table 3
MATRIX BACKREST WIDTH AVAILABLE RANGE RANGE

SEAT WIDTH (SW)	ELITE E2 / ELITE DEEP E2 MATRIX BACKREST WIDTH CHOICE						
	360 MM	380 MM	410 MM	430 MM	460 MM	480 MM	510 MM
320 MM							
340 MM							
360 MM							
380 MM							
400 MM							
420 MM							
440 MM							
460 MM							
480 MM							
500 MM							

SEAT WIDTH (SW)	MX2 MATRIX BACKREST WIDTH CHOICE						
	360 MM	380 MM	410 MM	430 MM	460 MM	480 MM	510 MM
320 MM							
340 MM							
360 MM							
380 MM							
400 MM							
420 MM							
440 MM							
460 MM							
480 MM							
500 MM							

Table 2 :
Frame type/angle/length, rear wheel size, lower leg length, FSTF, footrest type

Frame	24" rear wheel				25" rear wheel				26" rear wheel			
	LLL				LLL				LLL			
	FSTF	to bracket	footrest	flip-up	FSTF	to bracket	footrest	flip-up	FSTF	to bracket	footrest	flip-up
75° Short	450		330-420	290-420	460		330-430	290-430	470		330-440	290-440
	460		340-430	300-430	470		340-440	300-440	480		340-450	300-450
	470		350-440	310-440	480		350-450	310-450	490		350-460	310-460
75° Standard	480	S	370-450	330-450	490	S	370-460	330-460	500	S	370-470	330-470
	490	S	380-460	340-460	500	S	380-470	340-470	510	S	380-480	340-480
	500	L	390-470	350-470	510	L	390-480	350-480	520	L	390-490	350-490
75° +50mm	500	S	390-470	350-470	510	S	390-480	350-480	520	S	390-490	350-490
	510	S	400-480	360-480	520	S	400-490	360-490	530	S	400-500	360-500
	520	L	410-490	370-490	530	L	410-500	370-500	540	L	410-510	370-510
90° Short	450	S	330-410	290-410	460	S	330-420	290-420	470	S	330-430	290-430
	460	S	340-420	300-420	470	S	340-430	300-430	480	S	340-440	300-440
	470	S	350-430	310-430	480	S	350-440	310-440	490	S	350-450	310-450
90° Standard	480	S	380-440	340-440	490	S	380-450	340-450	500	S	380-460	340-460
	490	S	390-450	350-450	500	S	390-460	350-460	510	S	390-470	350-470
	500	L	400-460	360-460	510	L	400-470	360-470	520	L	400-480	360-480
90° +50mm	500	S	400-460	360-460	510	S	400-470	360-470	520	S	400-480	360-480
	510	S	410-470	370-470	520	S	410-480	370-480	530	S	410-490	370-490
	520	L	420-480	380-480	530	L	420-490	380-490	540	L	420-500	380-500
75° tapered	480	S	370-450		490	S	370-460		500	S	370-470	
	490	S	380-460		500	S	380-470		510	S	380-480	
	500	L	390-470	NC	510	L	390-480	NC	520	L	390-490	NC
90° tapered	480	S	390-440		490	S	390-450		500	S	390-460	
	490	S	400-450		500	S	400-460		510	S	400-470	
	500	L	410-460	NC	510	L	410-470	NC	520	L	410-480	NC