

Please contact Invacare EU Export Customer Services on :-
Tel : +33 247 626980 ; Email : serviceclient_export@invacare.com
Or visit our website : www.invacare.eu.com



Invacare® Action® Ampla™

Manual bariatric wheelchair



Date :

Purchase Order :

Customer Code :

Distributor Stamp::



Description:

- Aluminum wheelchair, rigid frame
- Folding backrest on the seat with lockable function
- Standard height-adjustable transfer handles
- New option: system for moving the chair vertically
- Weight: from 27 kg
- Maximum user weight: 300 kg
- 2-year warranty period excluding wear parts



nvacare Unique Customization Service
Please specify the quote or special production number:

☐ Please make your selection with a cross in the box ☒ Standard feature ☐ Free of charge option

CODE		DESCRIPTION	NC : Non Compatible NC : 9999 = not compatible with the reference 9999	Euros	
SMB0001	☐	Invacare® Action® Ampla™		4316,59	
SMBSPEC	☐	Special manufacture, compulsory for special colors		On Request	
PROPULSION TYPE					
SMB0500	☐	SELF PROPULSION		☒	
SEAT					
SEAT WIDTH					
SMB1000	☐	505 mm	NC : 5010	☐	
SMB1010	☐	555 mm		☐	
SMB1020	☐	605 mm		☐	
SMB1030	☐	655 mm	System for moving the wheelchair vertically through doors RECOMMENDED - option 9060	☐	
SMB1040	☐	705 mm		☐	
SMB1050	☐	755 mm		☐	
Seat depth - see drawing on the right Usable depth (A) = distance between edge of seat cover and front edge of backrest cushion Total depth (B) = distance between edge of seat cover and front of backrest tubes					
SMB1100	☐	WHEELCHAIR EFFECTIVE DEPTH 460 MM / 18" (A) – BACKREST FIXATION DEPTH 495 MM / 19,5" (B)		☐	
SMB1110	☐	WHEELCHAIR EFFECTIVE DEPTH 510 MM / 20" (A) – BACKREST FIXATION DEPTH 545 MM / 21,5" (B)		☐	
SEAT HEIGHT IN FRONT (FSTF) OF THE CHAIR, MEASURED FROM FLOOR TO CENTER OF SEAT					
SMB1200	☐	HEIGHT 380-405 MM / 15"-16" SET AT 380 MM / 15"		☐	
SMB1210	☐	HEIGHT 380-405 MM / 15"-16" SET AT 405 MM / 16"		☐	
SMB1220	☐	HEIGHT 430-455 MM / 17"-18" SET AT 430 MM / 17"		☐	
SMB1230	☐	HEIGHT 430-455 MM / 17"-18" SET AT 455 MM / 18"		☒	
SEAT TYPE					
SMB1300	☐	SEAT UPHOLSTERY		☒	
BACKREST					
BACKREST TYPE					
SMB2000	☐	FOLD DOWN, HEIGHT ADJUSTABLE 450-525 MM (STEP 25MM) / 17"-20" (STEP 1") SET AT 450 MM / 17"		☒	
SMB2010	☐	FOLD DOWN, HEIGHT ADJUSTABLE 450-525 MM (STEP 25MM) / 17"-20" (STEP 1") SET AT 500 MM / 19"		☐	2000 / 2010
SUPPORT TYPE					
SMB2100	☐	FIXED BACKREST CUSHION		☒	2100
HANGERS/FOOTPLATES					
HANGERS RH TYPE					
SMB3110	☐	SWING IN/OUT RH HANGER		☒	
HANGERS LH TYPE					
SMB3210	☐	SWING IN/OUT LH HANGER		☒	3110 / 3210



FOOTPLATES RH TYPE - INCLUDE ADJUSTABLE HEELSTRAP						
SMB3400	☐	FLIP UP RH FOOTPLATE ANGLE AND DEPTH ADJUSTABLE ON SHORT TUBE ULL 365 TO 445 MM	NC : 3550, 3570	☐	 4110 / 4210	
SMB3420	☐	FLIP UP RH FOOTPLATE ON SHORT TUBE ULL 365 TO 445 MM	NC : 3550, 3570	☒		
SMB3450	☐	FLIP UP RH FOOTPLATE ANGLE AND DEPTH ADJUSTABLE ON LONG TUBE ULL 445 TO 525 MM	NC : 3500, 3520	☐		
SMB3470	☐	FLIP UP RH FOOTPLATE ON LONG TUBE ULL 445 TO 525 MM	NC : 3500, 3520	☐		
FOOTPLATES LH TYPE - INCLUDE ADJUSTABLE HEELSTRAP						
SMB3500	☐	FLIP UP LH FOOTPLATE ANGLE AND DEPTH ADJUSTABLE ON SHORT TUBE ULL 365 TO 445 MM		☐		
SMB3520	☐	FLIP UP LH FOOTPLATE ON SHORT TUBE ULL 365 TO 445 MM		☒		
SMB3550	☐	FLIP UP LH FOOTPLATE ANGLE AND DEPTH ADJUSTABLE ON LONG TUBE ULL 445 TO 525 MM		☐		
SMB3570	☐	FLIP UP LH FOOTPLATE ON LONG TUBE ULL 445 TO 525 MM		☐		
TRANSFER HELP						
TRANSFER HELP RH FORM						 4110 / 4210
SMB4110	☐	TRANSFER HELP RH (INCLUDING MUDGUARD)		☒		
TRANSFER HELP LH FORM						
SMB4210	☐	TRANSFER HELP LH (INCLUDING MUDGUARD)		☒		
SEATING OPTIONS TYPE (Maximum width is 30")						
SMB5000	☐	STANDARD CUSHION (560 MM DEPTH, HEIGHT 60 MM) - MAX 300 Kg		138,31		
COLOURS / PERSONNALISATION						
FRAME COLOUR						
SMB6000	☐	TECH WHITE		☐		
SMB6010	☐	TECH GREY		☐		
SMB6099	☐	SPECIAL COLOUR		On Request		
STICKER						
SMB6500	☐	BLUE PULSE		☐		
SMB6510	☐	PINK PULSE		☐		
SMB6520	☐	GREEN PULSE		☐		
FRONT WHEELS						
SMB7000	☐	125 X 35 MM (5" X 1.3/8") BLACK SOLID TYRE, BLACK RIM		☒		
SMB7010	☐	150 X 35 MM (6" X 1.3/8") BLACK SOLID TYRE, BLACK RIM		☐		
REAR WHEELS						
SMB7100	☐	610 x 25 MM (24" X 1") STANDARD, BLACK SOLID TYRE, BLACK COMPOSITE FIVE SPOKES, BLACK ALU HANDRIM		☒	 7100	
REAR WHEELS AXLES TYPE						
SMB7200	☐	QUICK RELEASE AXLE		☒		
BRAKES TYPE						
SMB8000	☐	PUSH TO LOCK BRAKES	NC : 8010	☒		
SMB8010	☐	ATTENDANT RUNNING BRAKES WITH PUSH TO LOCK (INCLUDE HEIGHT ADJUSTABLE PUSHBAR)	NC : 9000, 9050	406,64		
SAFETY OPTIONS TYPE						
SMB8500	☐	TRANSPORTATION KIT	NC : 9020, 9030, 9040	198,10	 8520	
SMB8510	☐	POSTURE BELT - PLASTIC BUCKLE		73,93		
SMB8520	☐	ANTI-TIPPER PAIR	NC : 9060	306,16		
ATTENDANT OPTIONS TYPE						
SMB9000	☐	RH CANE HOLDER	NC : 9010, 9020	185,78	 9000/10 9040 9020/30 9050 9060	
SMB9010	☐	LH CANE HOLDER	NC : 9030	185,78		
SMB9020	☐	RH DRIP STAND (INCLUDE HEIGHT ADJUSTABLE PUSHBAR)	NC : 9030, 9050	532,70		
SMB9030	☐	LH DRIP STAND (INCLUDE HEIGHT ADJUSTABLE PUSHBAR)	NC : 9050	532,70		
SMB9040	☐	OXYGEN BOTTLE HOLDER		304,27		
SMB9050	☐	HEIGHT ADJUSTABLE PUSHBAR		304,27		
SMB9060	☐	TRANSPORTATION BEARINGS (ANTI-TIPPER FUNCTION)	RECOMMENDED for seat widths from 605mm to 755mm	532,70		

Table 1: Front and rear seat height

1°seat angle		Front seat height (FSTF)			
	(MM)	380	405	430	455
Rear seat height (RSTF)	370	○			
	395		○		
	420			○	
	445				○

Table 2:

Setting footplate height with long tube					
Seat height	ULL				
	445	465	485	505	525
380					
405					
430					
455					