

Invacare® Action®²_{NG} Transit Lite



Please contact Invacare EU Export Customer Services on :
Tel : +33 247 626980 ; Email : serviceclient_export@invacare.com
Or visit our website : www.invacare.eu.com



Invacare® Action®²_{NG} Transit Lite



Alluminum push wheelchair crossbar folding



- Description:**
- Seat height: 485 / 510 mm
 - Half height folding backrest , height: 430 mm
 - Seat depth: 400 mm
 - Overall width = seat width + 100 mm
 - Overall length: 995 mm
 - Rear wheels 12", black solid tyres with fixed axes
 - Front wheels 7" black solid tyres
 - Attendant cable brakes with parking and user brakes
 - Swing away and detachable desk armrests
 - Tippers and serial posture belt
 - Weight: 13,4 kg
 - User maximum weight: 125 kg
 - 2 years of warranty excluding wear parts

Date :

User name :

Client code :

Distributor's stamp :

						Euros		
						Public Price		
						HT		
Quantity								
Invacare [®] Action ^{® 2} NG Transit Lite - Folding backrest at mid-height								
12" Rear wheels - Black solid tyres - Select the seat width and the quantity								
BR1673114		405 mm	338,33					
BR1673115		430 mm						
BR1673116		455 mm						
BR1673117		480 mm						
Accesories (Separately delivered)								
60 mm foam cushion - nylon cover with anti-slip basis - for seat width								
1564267		405 mm / 430 mm (412 mm x 412 mm)				33,08		
1564268		455 mm / 480 mm (462 mm x 412 mm)				33,08		
Standard legrests with adjustable footplates - Select a width - Supplied with heel straps								
1573661		405 mm / 430 mm				200,49		
1573692		455 mm/ 505 mm				200,49		
Cane holder								
AP0572-02056		Kit cane holder				49,29		
Amputee legrest								
AP1442990		Amputee legrest right				140,28		
AP1442991		Amputee legrest left				140,28		
Anti-tippers (Pair)								
AP1673828		Anti-tippers pair				77,73		
Neckrest with backbrace - for seat width								
AP1673830		405 mm	AP1673832		455 mm	60,10		
AP1673831		430 mm	AP1673833		480 mm	60,10		
Drip-stand-rod with backbrace - Select a width and the quantity								
AP1673836		405 mm	AP1673838		455 mm	97,63		
AP1673837		430 mm	AP1673839		480 mm	97,63		