

Please contact Invacare EU Export Customer Services on :-
Tel : +33 247 626980 ; Email : serviceclient_export@invacare.com
Or visit our website : www.invacare.eu.com

Invacare® Esprit Action

Folding electric wheelchair - with removeable parts.



NEW GENERATION with standard gyroscope

- Electric wheelchair folding by crossbar and parts removeable without tools. Standard :
- Automatic adjustment of the accelerations thanks to an integrated gyroscope
- 14" rear wheels with black tires and gripping handles for easy disassembly
- Front wheels 8" black tire or tread- Speed 6 km/h or 8 km/h
- Gel battery, autonomy 15 km- Joystick with color screen, on-board computer and light
- Reduced space requirement thanks to a 50 mm shorter wheelbase
- Weight: from 40,3 kg complete - heaviest element: from 13,8 kg
- 2-year warranty excluding battery and wearing parts.

Class B homologation

with the option SPC0620 Mounted additional battery 7,65Ah/6V with bag



Date :

Purchase order:

Customer code :

Dealer stamp :


☐ Please make your selection with a cross in the box

◆ Standard feature

○ Free of Charge

Please mark your selection with a cross in the box			Standard version		Accessories	
CODE		DESCRIPTION	NC : 9999 : non compatible avec la référence 9999	Euros	 Anti-tilt	
SPC0110	☐	Invacare® <i>Esprit Action</i>		3 306,11		
SPC0120	☐	Invacare® <i>Esprit Action PACK</i> - Make disassembly easy! - includes double intuitive single control (one handle) and antitipper with kickstand function	NC: 0440, 0450, 0460, 0640, 8000, 8010	3 983,14		
FRAME						
SPC0200	☐	Single cross-brace (Seat width from 305 mm to 380 mm / Depth from 325 to 375 mm) - Maximum user weight: 80 kg.	NC : 1040, 1050, 1060, 1070, 1080, 1090, 1100, 1110, 1210, 1220, 1230, 1240, 1250, 1410, 2070, 2090, 2100, 2200, 2210, 2220, 2230, 2310, 2330, 3020, 3030, 3120, 3130, 4020, 4120, 5010, 5020, 5030, 5040, 5042, 5044, 5046, 5048, 5050, 5060, 5070, 5100, 5130, 5170, 6030, 6040	○		
SPC0210	☐	Double brace (Seat width from 380 mm to 605 mm / Depth from 400 to 500 mm) - Max. user weight: 125 kg.	NC : 1000, 1010, 1020, 1030, 1200, 1400, 3000, 3100, 5000, 5160, 6020	◆		
ELECTRONIC CONTROLS						
Joystick with color display, charge, autonomy and speed indicator, integrated lighting and palm rest						
Main control - type of support						
SPC0300	☐	Retractable to the outside		◆	344,08	
SPC0310	☐	Inward and outward retractable, multi-adjustable (type E-Fix E35)				
Main control - mounting side					 0310	
SPC0400	☐	Retractable right side	NC : 4020	◆		
SPC0410	☐	Retractable left side	NC : 4120	○		
Dual intuitive controls						
SPC0440	☐	Dual intuitive right-hand controls, 2 handles	NC : 0640	677,02		
SPC0450	☐	Double intuitive left-hand control, 2 handles	NC : 0640	677,02		
SPC0460	☐	Simple intuitive dual control, one handle (adjustable right/left)	NC : 0640	677,02		
SPEED						
SPC0500	☐	6 km/h		◆		
SPC0510	☐	8 km/h- Not compatible with custom programming		364,93		
BATTERIES						
SPC0600	☐	Gel battery - Autonomy 15 km		◆		
ELECTRICAL OPTIONS						
SPC0610	☐	Additional Gel Battery		492,89	 0630	
SPC0620	☐	Mounted additional battery 7,65Ah/6V with bag		615,17		
SPC0630	☐	Joystick protection		75,83		
SPC0640	☐	Additional remote load socket (extension cable)		108,06		
1490794	☐	UK power cable		○		

SEAT				
Seat width for single brace (SPC0200 / adjustable between armrests)				
SPC1000	☐	305 mm - Adjustable from 305 mm to 355 mm		○
SPC1010	☐	330 mm - Adjustable from 330 mm to 380 mm		○
SPC1020	☐	355 mm - Adjustable from 355 mm to 405 mm		○
SPC1030	☐	380 mm - Adjustable from 380 mm to 430 mm		○
Seat width for double brace (SPC0210 / adjustable between armrests)				
SPC1040	☐	380 mm - Adjustable from 380 mm to 430 mm	NC : 1240, 1250, 2100, 5046	○
SPC1050	☐	405 mm - Adjustable from 405 mm to 455 mm	NC : 1240, 1250	○
SPC1060	☐	430 mm - Adjustable from 430 mm to 480 mm	NC : 5042	◆
SPC1070	☐	455 mm - Adjustable from 455 mm to 505 mm	NC : 5042	○
SPC1080	☐	480 mm - Adjustable from 480 mm to 530 mm	NC : 2100, 2330, 5042, 5044	○
SPC1090	☐	505 mm - Adjustable from 505 mm to 555 mm	NC : 5042, 5044, 5046, 5048	○
SPC1100	☐	555 mm - Adjustable from 555 mm to 605 mm	NC : 1210, 2100, 2200, 2210, 2220, 2230, 2330, 5020, 5030, 5040, 5042, 5044, 5046, 5048, 5050, 5080, 5130, 8200	436,97
SPC1110	☐	605 mm - Adjustable from 605 mm to 655 mm	NC : 1210, 2100, 2200, 2210, 2220, 2230, 2330, 5020, 5030, 5040, 5042, 5044, 5046, 5048, 5050, 5060, 5070, 5080, 5130, 8200	436,97
Seat depth				
SPC1200	☐	Adjustable by scratch from 325 to 375 mm, for simple crosspiece (set at 350 mm)		○
SPC1210	☐	400 mm	NC : 5085, 5090	◆
SPC1220	☐	Adjustable by scratch from 400 to 450 mm	NC : 5090	27,49
SPC1230	☐	450 mm	NC : 5042, 5080, 5090	○
SPC1240	☐	Adjustable by scratch from 450 to 500 mm	NC : 5042, 5080	191,47
SPC1250	☐	500 mm	NC : 5042, 5044, 5046, 5048, 5080	164,93
Seat height floor to seat				
SPC1300	☐	460 mm		◆
SPC1310	☐	485 mm		○
Seat cover				
SPC1400	☐	Black nylon with Velcro - adjustable in width and depth		○
SPC1410	☐	Black nylon with Velcro (for double brace only)		◆
BACKREST				
Reclining backrest				
SPC2040	☐	Adjustable in angle (-15° to +15°) and foldable - height 425 mm - with long handles and folding backrest tensioner at mid-height	NC : 2330	446,45
SPC2050	☐	By cylinders 0° to 30° and folding at half height with tensioner - height 430 mm - fabric adjustable to 390 and 410 mm	NC : 2200, 2210, 2220, 2230, 2330	64,45
SPC2060	☐	By rack 0° to 30° with tensioner - height 430 mm - adjustable to 390 and 410 mm.	NC : 2330	○
SPC2070	☐	By rack 0° to 30° with tensioner - height 510 mm - adjustable to 470 and 490 mm	NC : 2330	◆
SPC2080	☐	By cylinders 0° to 30° with tensioner - height 430 mm - adjustable canvas at 390 and 410 mm	NC : 2330	289,10
SPC2090	☐	By cylinders 0° to 30° with tensioner - height 510 mm - adjustable to 470 and 490 mm	NC : 2330	289,10
SPC2100	☐	By pneumatic cylinders 0° to 30° with tensioner - height 510 mm for Passad 2 comfort backrest	NC : 2200, 2210, 2220, 2230, 2300, 2310, 2320, 8030	289,10
Matrx backrest - The width of the backrest matches the width of the seat. Ex: seat width 430 = Matrx Elite backrest width 430 mm - Delivery time: +5 days Find the backrests and all the accessories on the Matrx pricelist!				
SPC2200	☐	Matrx Elite E2, height 405 mm	NC: 2300, 2310, 2320, 2330, 5140	717,54
SPC2210	☐	Matrx Elite E2, height 455 mm	NC : 2300, 2310, 2320, 2330, 5140	717,54
SPC2220	☐	Matrx Elite Deep E2, height 405 mm	NC: 2300, 2310, 2320, 2330, 5140	717,54
SPC2230	☐	Matrx Elite Deep E2, height 455 mm	NC: 2300, 2310, 2320, 2330, 5140	717,54
Caution - Loss of about 20 mm of seat depth with tiltable backrests				
Backrest upholstery - NEW design				
SPC2300	☐	Padded, adjustable tension (1 strap), black nylon and breathable fabric	NC : 5130	◆
SPC2310	☐	Padded, adjustable tension (4 straps), black nylon and breathable fabric (for double brace only)	NC : 5130	54,03
SPC2320	☐	Padded, adjustable tension (10 straps), black nylon and breathable fabric	NC : 5130	135,55
SPC2330	☐	Passad 2 comfort backrest with black biextensible PU coating, height 510 mm (for double crosspiece only)	NC : 5130, 5140	305,21

FOOT/LEG RESTS					 3010 / 3110	
Stem, right leg rest						
SPC3000	☐	80° short stem, UL 200 to 330 mm (single bar only)	NC : 3110			
SPC3010	☐	80° long stem, UL 340 to 47 mm (double crossbar only)	NC : 3100			
SPC3020	☐	Leg rest adjustable in inclination from 0° to 75°, UL 340 to 500 mm	NC : 3220, 5150	181,04		
SPC3030	☐	Amputee support	NC : 3200, 3210, 3220	181,04		
Stem, left leg rest					 3020 / 3120	
SPC3100	☐	80° short stem, UL 200 to 330 mm (single bar only)				
SPC3110	☐	80° long stem, UL 340 to 47 mm (double crossbar only)				
SPC3120	☐	Leg rest adjustable from 0° to 75°, UL 340 to 500 mm	NC : 3220, 5150	181,04		
SPC3130	☐	Amputee support	NC : 3220, 3300, 3310	181,04		
Lifting footplate, right					 3030 / 3130	
SPC3200	☐	Fixed with heel strap				
SPC3210	☐	Adjustable in depth and inclination with heel strap		31,28		
SPC3220	☐	One-piece, adjustable in depth and angle and fully liftable with calf support strap	NC : 3300, 3310	218,01		
Lifting footplate, left						 3210 / 3310
SPC3300	☐	Fixed with heel strap				
SPC3310	☐	Adjustable in depth and inclination with heel strap		31,28		
ARMRESTS					 4000 / 4100  4020 / 4120	
Adjustable in height from 210 to 345 mm according to cuff, depth of 35 mm, width of 25 mm on the right side						
SPC4000	☐	Removable armrest, short cuff 280 mm	NC : 8200			
SPC4010	☐	Removable armrest, long cuff 380 mm		38,86		
SPC4020	☐	Removable armrest, concave trough and indexed lateral rotation system (self-locking)	NC : 8200	155,45		
Adjustable in height from 210 to 345 mm according to cuff, in depth of 35 mm, in width of 25 mm on the left side					 4020 / 4120	
SPC4100	☐	Removable armrest, short cuff 280 mm	NC : 8200			
SPC4110	☐	Removable armrest, long sleeve 380 mm		38,86		
SPC4120	☐	Removable armrest, concave channel and indexed lateral rotation system (self-locking)	NC : 8200	155,45		
SEATING OPTIONS						
SPC5000	☐	Foam seat cushion Essential junior, height 50 mm	NC : 5080, 5085, 5090			
SPC5010	☐	Foam seat cushion, black nylon cover with non-slip base, 50 mm thick				
SPC5020	☐	Matrx Flo-tech Lite seat cushion, 78 mm thick	NC : 5090			
SPC5030	☐	Matrx Flo-tech Image (gel) seat cushion, thickness 60 mm	NC : 5090	201,90		
SPC5040	☐	Matrx Contour ViscoNG seat cushion, thickness 100 mm, max. user weight 100 kg	NC : 5090	76,78		
SPC5042	☐	Seat cushion Classic Visco 75 mm thick, 375 mm x 400 mm	NC : 5080, 5085, 5090	76,78		
SPC5044	☐	Seat cushion Classic Visco 75 mm thick, 405 mm x 400 mm	NC : 5080, 5085, 5090	65,40		
SPC5046	☐	Seat cushion Classic Visco 75 mm thick, 430 mm x 430 mm	NC : 5080, 5085, 5090	65,40		
SPC5048	☐	Seat cushion Classic Visco 75 mm thick, 455 mm x 400 mm	NC : 5080, 5085, 5090	76,78		
SPC5050	☐	Seat cushion Matrx Flo-tech Solution Xtra thickness 60 mm	NC : 5090	323,22		
SPC5070	☐	Matrx Libra seat cushion, 70 mm thick		293,84		
Cushion depth						
SPC5080	☐	400 mm				
SPC5085	☐	450 mm				
SPC5090	☐	500 mm				

Other options					
SPC5100	☐	Neck support, including backrest tensioner		82,46	 5100  5110  5120  5140  5130
SPC5110	☐	Headrest with adjustable earpieces, including backrest tensioner, laterally adjustable		178,20	
SPC5120	☐	Headrest with adjustable long earpieces - including backrest tensioner and lateral adjustment (for double cross-brace only)		191,47	
SPC5130	☐	Matrix headrest with 250 mm wide soft cushion - delivered with fixation (only for Matrix backrest)		374,41	
SPC5140	☐	Tension adjustable backrest cushion (pair) (cushion dimensions: width 35 mm, height 115 mm, depth 130 mm)		201,90	
SPC5150	☐	Calf support strap		10,43	
FRAME COLORS					
SPC6000	☐	Anthracite Black		○	
SPC6015	☐	Dark Purple		○	
SPC6020	☐	Ocean Blue	Single bar only	○	
SPC6035	☐	Navy Blue	Double brace only	○	
SPC6040	☐	Slate Gray	Double brace only	○	
SPC6050	☐	Special Colors		On demand	
COLOR KEYS					
SPC6100	☐	Black		◆	 
SPC6120	☐	Lemon Yellow (Forks + backrest support)		75,83	
FRONT WHEELS					
SPC7000	☐	8" x 2"- 200 x 50 mm, Black Solid tyre		○	
SPC7010	☐	8" x 2"- 200 x 50 mm, Black Pneumatic tyre		○	
REAR WHEELS					
SPC7100	☐	14" - 355 x 70 mm - Black Solid tyre		238,86	
SPC7110	☐	14" - 355 x 70 mm - Black Pneumatic tyre		◆	
SECURITY OPTIONS					
SPC8000	☐	Anti-tippers		◆	 8000  8010  8040
SPC8010	☐	Anti-tippers with kickstand function		436,97	
SPC8020	☐	Seat belt - (New design 2022)		◆	
SPC8030	☐	Cab hooks according to ISO7176-19: 2001 for the transport of persons, the batteries are to be removed when the chair is used as a seat in the vehicle		75,83	
SPC8040	☐	Rear light position		46,45	
POSITIONING OPTIONS					
Consider Bodypoint positioning accessories: belts, harnesses, ankle supports.					
VARIOUS OPTIONS					
SPC8100	☐	Cane holder		41,71	 8200
SPC8200	☐	Retractable transparent shelf - opposite side to the manipulator		276,78	
RAMPS					
1440530	☐	Fiberglass Folding Mono Ramp Folded dimensions: 2000 x 230 mm 16.3 kg - maximum capacity: 300 kg		1 787,68	 1440530
1654128	☐	Basic ramp 2 telescopic parts in aluminum and non-slip coating. Folded dimensions: 1210 x 194 mm. 8.8 kg per pair - maximum capacity: 270 kg		402,84	 165412
1654129	☐	Quick2go Compact 3-part aluminum telescopic ramp with non-slip coating Folded dimensions: 870 x 237 mm 13.6 kg per pair - maximum capacity: 260 kg		805,69	 165412
1654130	☐	Aluminium folding mono ramp Folded dimensions: 1824 x 714 mm 13.9 kg - maximum capacity: 300 kg		426,54	 1654130